

### DHG Series — Direct/Belt Drive



DHG-4004-D0H6G  
Direct Drive

*This powerful pressure washer series is built to blast away the toughest grease and grime. It features a 12V Beckett burner, bottom-fired heat exchanger and pneumatic tires.*

#### PUMP

- Adjustable stainless-steel and brass unloader valve
- Forged brass manifold
- Thermal relief valve

#### ENGINE

- Performance-proven OHV engine with low-oil protection
- 12V electric start – battery not included

#### FRAME

- Reinforced powder coated steel frame with center balanced lifting hook
- 15-inch pneumatic tires

#### COMPONENTS

- ½-inch schedule 80 pipe coil with 4-pancake bottom-fired heat exchanger
- 12V Beckett burner
- No. 1 or No. 2 diesel or kerosene fired burner (Not approved for bio-fuel)
- Adjustable temperature
- Hour meter

#### MISCELLANEOUS

- Temperature rise 130°F/54°C above ambient
- Water output temperature is 250°F in “wet” steam

#### UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- ¼-inch MEG and ¼-inch MQC wet steam nozzle – 25°
- 50-foot x ⅜-inch steel wire-braided high pressure hose
- Adjustable pressure insulated dual lance
- Professional-grade insulated trigger gun with safety lock-off
- External downstream detergent injector with detergent nozzle

#### LIMITED WARRANTY

- 3 year engine



**Exclusive  
Dealer  
Product**

# Portable Gasoline

## Hot Water – DHG Series – Direct/Belt Drive

### DIRECT DRIVE MODELS

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DHG-4004-D0H6G	4000	3.7	389cc Honda GX390 OHV <sup>+</sup>	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	49.5x30x48in.	601 lb.	478 lb.
DHG-4004-D0V6G	4000	3.7	408cc Vanguard OHV	General	1.52 gallons	10.0 gallons	2.14 gph	299,600	49.5x30x48in.	596 lb.	466 lb.

### BELT DRIVE MODELS

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU PER HOUR	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DHG-4004-B0H6G	4000	3.7	389cc Honda GX390 OHV <sup>+</sup>	General	1.61 gallons	10.0 gallons	2.14 gph	299,600	49.5x30x48in.	643 lb.	520 lb.
DHG-4004-B0V6G	4000	3.7	408cc Vanguard OHV	General	1.52 gallons	10.0 gallons	2.14 gph	299,600	49.5x30x48in.	641 lb.	511 lb.

Note: All gasoline models sold in California are required to have a CARB compliant engine. Consult factory.

<sup>+</sup>49 state engine. Not for sale in California.

### ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0195	Hose reel – 13-inch, 150-foot maximum hose length	All models
50-0196	Hose reel – 16-inch, 200-foot maximum hose length	All models
AW-6000-1006	Hot water equipment cover – Keeps your equipment clean, dry and looking like new; made from 600-denier vinyl-back polyester, water resistant, drawstrings to secure cover; Mi-T-M logo	All models
AW-6000-1007	Hot water equipment cover – Keeps your equipment clean, dry and looking like new; made from 600-denier vinyl-back polyester, water resistant, drawstrings to secure cover; no logo	All models

### OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
HX-0273	Stainless-steel coil wrap – Converts powder coated painted coil wrap to stainless-steel material	All models
HX-0278	Skid feet – Stationary applications	All models



DHG-4004-B0H6G belt drive shown with stainless-steel coil wrap option, HX-0273

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).